# ELEVATOR & CONVEYOR



Galvanised and bolted **FIXED or MOVEABLE** with adjustable height

**FIXED** ELEVATOR






**Exit Carpet for Dryer** 



**TSP** flat carpet



Manufacturer of solutions for the harvest and work of the fruits

**TDC Carpet Distributor** for Dryer



AMB Rousset impasse du Tilleul 38470 BEAULIEU - France



Tél: +33 (0) 4 76 36 73 73 Fax: +33 (0) 4 76 36 70 82 E-mail: export@ambrousset.com

www.amb-rousset.com



### **Technical specifications**

	ELB	TGB				
Yield	Flow rate from 3 to 10 tonnes*/hour * Depending on product	Flow rate from 3 to 20 tonnes*/hour * Depending on product				
Motorization	Three-phase geared motor (1.1 kW) with fixed or variable speed by me	echanical variator. Left in the direction of the product				
		2 motors from 17m (4040024)				
Frame	Galvanized structure bolted in sections of 0.50m or 1m screwed in bent sheet metal					
	Band width: 300, 400, 500 or 600 mm					
Conveyor belt	PVC strip (green) with straight PVC cleats h60 not 150mm for 45 ° / 60 ° elevator.  PVC band (green) with inclined PVC cleats h60 not 120mm for 80 ° / 90 ° elevator.	Smooth green PVC tape				
	1-point web tension by translation of the head roller	Band tension at both ends by translation of the rollers				
Hopper	Hopper included with no added value: Standard hopper width 1m or Micro hopper					
Drum	Domed machined drive drum for good belt centering					
Holding rollers		Conveyor belt retaining roller for very long TGB 4 to 5m: 1 roll / 6 to 8m: 2 rolls 9 to 11m: 3 rolls /> 12m:: 4 rolls				
Security	Mechanical and bucket belt fully protected under housing (In accordance with labor legislation)  Complies with CE standards					
Length	from 1.50 m to 9 m in steps of 0.5m	from 2.50 m to 24 m in steps of 0.5m				
Width	300 - 400 - 500 - 600 mm					
Height	adjustable					
Weight	depending on model (depending on length and width)					
<b>OPTIONS</b>						
Hopper	<ul> <li>✓ Hopper: - MICRO hopper</li> <li>- Standard hopper</li> <li>- Straight hopper with removable extension (front or side entry)</li> <li>- Hopper width 1 m 80</li> <li>- Hopper width 2 m 60</li> </ul>					
171	✓ Debris scraper kit under lower belt					
Kit	✓ SAE mounting kit					
Trolley and feet	✓ ECO trolley - Polyamide wheel model without ECO elevator bearing + height adjustment by slide (ELB0005) ✓ Trolley for ELB up to 6m - Wheel on Ø400 bearing + height adjustment by winch ✓ Fixed foot for elevator (often used on waste) (ELE0199)	✓ Feet (ELB0033) up to 7m = 2 feet > 7m = 1 foot every 3m max				
Conveyor belt	✓ Sealing strip on the 2 sides of the belt ✓ Food strip ✓ Strip with containment edge					
Mechanical variator	✓ MotoVario Mechanical gearbox (ELE0045)					
Electronic variator	✓ Electronic dimmer (all width)					
Inverter		✓ Inverter (4560002)				
Length	✓ Length: 9.50 m to 10.50 m in steps of 0.5 m (fixed without carriage)					

## **ELEVATOR & CONVEYOR**

#### → HOPPER

	ELEVATOR	300 mm	400 mm	500 mm	600 mm
HOPPER	MICRO	ELE0188	ELE0189	ELE0212	ELE0207
	1 M (standard)	ELE0156	ELE0194	ELE0213	ELE0209
	0,40 M (droite)	ELE0206			
	0,50 M (droite)		ELE0198		
	0,60 M (droite)			ELE0217	
	0,70 M (droite)				ELE0210
	1,80 M	ELE0002			
	2,60 M	ELE0003	ELE0185		



Hopper 2 600mm (ELE0003 et ELE0185)

Hopper 1 800mm (ELE0002)

**Hopper MICRO** (ELE0188 - ELE0189-ELE0212-ELE0207)

Hopper STANDARD (ELE0156 - ELE0194-ELE0213-ELE0209)




Straight hopper with extension (ELE0206 - ELE0198-ELE0217 - ELE210)

#### **Conveyor belts**



**Edged carpet** sealing (ELB0140)



Carpet with border of capacity and food strip (ELB0139 et ELE0205)

#### → Trolleys



on mobile cart

elevator **Elevator** 

Small model (ELE0157) (for ELB 3m and 3m50) Medium model (ELE0158) (for ELB 4m and 4m50) Big mobil modèel (ELE0159) (for ELB 5m to 6m)

## ELEVATOR & CONVEYOR L B

### → Carpet



**TSC**Drying Cell Outlet Carpet



TDC
Drying Cell Distributor Carpet



Carpet feet
Option ELB003



Distribution gate with cable control



**Cell distributor Carpet** Supplied as a kit per 6m module