

KG K7



Manufacturer of solutions for the harvest and work of the fruits



A M B Rousset impasse du Tilleul 38470 BEAULIEU - France



Tél : +33 (0) 4 76 36 73 73 Fax : +33 (0) 4 76 36 70 82 E-mail : export@ambrousset.com www.amb-rousset.com

TK6-AUD-L05-023570\_0B

# RESERVING HOPPER For emptying the trailer

## **Technical specifications**

- Very robust welded mechanic painted frame.
- Assembly on 4 landings automobile-aligners
- Motor-reducer three-phase in variable speed by variator (0,55 Kw)

#### Working

- 4 m belt hopper.
- PVC conveyor belt 500 mm wide with PVC cleats (pitch: 1,870 mm, height: 8 mm).
- Adjustment of the belt tension.
- Belt speed adjustment by mechanical variator.
- The 2.92 m wide hopper allows the trailer to be emptied.
- Fixed flat iron grid on the field.

### **Elevator (option)**

- Length: on request.
- Width: 500 mm.
- PVC conveyor belt width 480 mm. With PVC cleats (pitch: 150 mm, height: 60 mm).

#### Weight and dimensions

- Length: total: 4.150 m emptying width: 2.92 m
- Width: 1.09 m
- Height: from 0.60 to 0.90 m
- Weight: 530 kg





