INSPECTION TABLE



Manufacturer of solutions for the harvest and work of the fruits

Kernels



A M B R o u s s e t impasse du Tilleul 38470 BEAULIEU - France



Tél: +33 (0) 4 76 36 73 73 Fax: +33 (0) 4 76 36 70 82 **E-mail:** export@ambrousset.com

www.amb-rousset.com



Main Features

This sorting table is intended for manual fruit sorting.

For nuts, it's used to separate the good from the bad nuts. It's also used to separate the shells from the kernels after breaking.

The height of the table and the speed are adjustable in order to offer you maximum working comfort.

Technical characteristics

	TA1		TA2	
	TA10001	TA10002	TA20001	TA20002
Length	2M	3M	2M	3M
Yield				
Width	500		500	
Motorization	Three-phase geared motor 0.18Kw 7.4 at 40Tr / min		Three-phase geared motor 0.18Kw 5.6 to 30Tr / min	
Chassis	Galvanized-bolted structure in bent sheet metal			
Conveyor belt	Food grade PVC band with notched guide profile		Food blue PU tape with smooth guide profile	
	Tensioner with cast iron bearing, grease nipple and through shaft		Tensioner with permanently greased sheet metal bearing and through shaft	
Rollers	I	PVC rolls diameter 115	ter 115	
maintenance	Return roller with fixed axis greased for life			
Product output	Tilting outlet chute			
Corridors	2 waste lanes 75mm wide Height 50mm		2 waste channels 60mm wide 8mm high (per guide profile)	
Waste outlet			2 side chutes with fixed waste with cover	
Feet	Adjustable galvanized feet for height from floor to mat 720 to 1070mm		Galvanized adjustable foot for a height from the floor to the 776 to 1076 mm	
Weight	120kg		150kg	
OPTIONS				
Width	600mm TA10006	600mm TA10007	600mm TABLE CASCADE INOX TA30001	
	400mm (without variator) TA10003			
Length	Length 4M - Width 500mm TA10012		2 mats of 1.30M	
Width and length	Length 4M - Width 800mm TA10005			
Corridor	1 corridor only 2 corridors width XX			