

ELO Containment edge



ELO 45/60° or 80/90°



**ELO
Flat conveyor (TSP)**



ELO Dryers exit conveyor (TSC)



ELO Dryers distributor (TDC)

Manufacturer of solutions for the harvest and work of the fruits 

A M B Rousset
impasse du Tilleul
38470 BEAULIEU - France



Tél : +33 (0) 4 76 36 73 73
Fax : +33 (0) 4 76 36 70 82
E-mail : export@ambrousset.com
www.amb-rousset.com

ELEVATOR & CONVEYOR **ELO**

Technical features

	ELEVATOR	CONVEYOR
Output	Depending on the inclination from 3 to 5 tons / hour	
Motor	Three-phase geared motor (0,37kW) fixed speed or variable with mechanic speed variator On the left in the fruit way	
Chassis	Galvanized structure bolted by sections of 1 or 1.5m screwed in folded sheets Axes mounted on 2 self-aligning bearings	
Belt	PVC belt with buckets (width 250mm, spacing of 136 mm) Adjustable tension	PVC belt green & smooth (width 250 mm) Adjustable tension
Driving drum	Machined rounded driving drum to center the belt	Machined rounded driving drum to center the belt
Holding Roller		Belt holding roller 1 roller every 3m
Security	Mecanic and belt with buckets fully protected under steel case Conforms to CE standards	
Length	from 2 to 7m (sections of 0,5 m)	
Width	Belt width 250 mm / 350 mm overall	
Height	Adjustable	
Weight	Depending on the length	
OPTIONS		
Belt	<ul style="list-style-type: none"> ✓ Food grade belt ✓ Containment edge belt 	<ul style="list-style-type: none"> ✓ Waterproofness on both side of the belt ✓ Food grade belt ✓ Containment edge belt
Hopper	<ul style="list-style-type: none"> ✓ Micro hopper (ELO0018) ✓ Standard hopper (ELO0019) ✓ Straight hopper removable extension (frontal or lateral input) (ELO0004) ✓ Stainless hopper (ELO0007) ✓ Stainless hopper extension (ELO0050) ✓ Low case to raise the hopper (ELO0017) 	
Channel		
Kit	<ul style="list-style-type: none"> ✓ Mounting kit on dryer or storage hopper (ELB0331) 	
Trolley & legs	<ul style="list-style-type: none"> ✓ ECO trolley from 2 to 3m ✓ Adjustable trolley from 3,5 to 5m ✓ Fixed foot 	<ul style="list-style-type: none"> ✓ Legs (1 leg every 3m) (ELO0021)
Dimmer switch	<ul style="list-style-type: none"> ✓ Mecanic ✓ Electronic 	
Kit		<ul style="list-style-type: none"> ✓ Reverser

ELO 45/60°

ELO 80/90°

Standard belt

Food grade blue belt

Containment edge belt

