

# SWEEPERS ON TRACTOR

# GIT



**Manufacturer of solutions for the harvest and work of the fruits** 

**A M B Rousset**  
impasse du Tilleul  
38470 BEAULIEU - France



Tél : +33 (0) 4 76 36 73 73  
Fax : +33 (0) 4 76 36 70 82  
E-mail : [export@ambrousset.com](mailto:export@ambrousset.com)  
[www.amb-rousset.com](http://www.amb-rousset.com)

## Technical features

### TECHNICAL FEATURES

Chassis : bolted, welded and painted

Diameter : Ø 740 mm

### FUNCTIONING

The sweepers on tractor move the fruit before the wheels.

Sweepers rotation by hydraulic drive

Hydraulic supply of the rotation by the tractor or by the distributor of the tool at the rear of the tractor (VHT, VHY, VHP, other...)

Raising and lowering of the sweepers by hydraulic jacks fed by a single-acting tractor distributor.

### ADVANTAGES

#### Fruits preservation

The sweepers follow the ground (bump or dent) thanks to their design with a parallelogram and a floating position of the jack.

The sweepers follow the wheels turn thanks to their hanging on the wheel pivots of the tractor.

#### Using

Sweepers speed adjustable

Quick disassembly of the sweepers : bolts, hydraulic connection with PUSH PULL plugs.

### WEIGHT

95 kg per sweepers : around 380 kg

